

AMENDMENTS TO THE SPECIFICATION

Please revise paragraphs ^[0048] [0047], ^[0049] [0048], and ^[0058] [0057] of Published Patent Application No. 2007/0092158 as follows:

^[0048] [0047] First, a line segment extraction unit (22) of the CPU (2) extracts a line segment segment (41) from a line-shaped image object (30) in the image at a step (10). Although any optional methods may be employed to separate the region of the line-shaped image-object object (30) from the image, when, for example, a line-shaped image-object object (30) has a predetermined shape, the line-segment segment (41) may be extracted according to the shape.

12/29
T.T.

^[0049] [0048] Then, a line-shaped image elimination unit (23) enlarges the line-segment segment (41) obtained at the above step and removes the line-segment segment (41) from a portion in which at least a moving object (31) is included in the image (line segment image elimination step (11)). It is needless to say that a line-shaped image object may be eliminated from the entire image. The eliminated image can be stored in the memory (3).

12/29
T.T.

^[0058] [0057] Further, as shown in ~~Fig. 6~~ Fig. 5, the pixels (42) on the line segment (41) may be sequentially scanned, screen coordinates (44), (44), (45), (45) (in this case, four types of screen coordinates exist to a single pixel (42)) may be determined by adding and subtracting a value, which is obtained by adding 1 to a size (43) one half the line width, to and from the screen coordinate of the pixel (42), which is obtained each time the pixels (42) are scanned,

12/29
T.T.